



GAS.BE – ARGB – KVBG

The GAS.BE-ARGB-KVBG laboratory certifies the conformity with Belgian requirements for
Le laboratoire GAS.BE-ARGB certifie que les raccords à sertir gaz sont conformes aux ex
Het laboratorium van de GAS.BE-KVBG verklaart dat de gas persfittings conform zijn aan d

Certificate Number :
N° du certificat :
Certificaat nummer : **C-20-3702-BA**

Date of issue :
Date d'édition :
Datum van aflevering : **15/10/2020**

Manufacturer :
Fabricant :
Fabrikant : **Viega Technology GmbH & Co. KG
Viega Platz 1
DE- 57439 Attendorn**

Distributor :
Distributeur :
Verdeler: **Viega Belgium
Planet I Business Park
Tollaen 101 c
BE- 1932 Sint-Stevens-Woluwe**

Type: **Profipress G**
Copper & Copper alloys gas press fittings for copper tubes pipes
(according to EN 1057)
Raccords à sertir en cuivre et alliages de cuivre pour tuyaux en cuivre (conforme à la EN 1057)
Koper & Koperlegering gas persfittings voor koperen buizen
(volgens EN 10312)

MOP: 5 bar - GT: 1 bar

Diameter: 12 – 15 – 18 – 22 – 28 – 35 – 42 – 54 mm

Thread EN 10226-1 R/Rp: 3/8" – 1/2" – 3/4" – 1" – 5/4" – 6/4" – 2"

Model 2616 : 90° elbow, female/female end

Model 2616.1 : 90° elbow, female end/plain male end

Model 2626 : 45° elbow, female/female end

Model 2626.1 : 45° elbow, female end/plain male end

Model 2614 : 90° adapter elbow, female end and male R thread

Model 2614.2 : 90° adapter knee, female end and female Rp thread

Model 2618 : Tee, female ends

Model 2617.2 : Tee, with female Rp thread and female/female end

Model 2618.1 : Tee, with male and female/female end

Model 2611 : Adapter, with female end and male R thread

Model 2211.1 : Adapter, with plane male end and male R thread

Model 2212.1 : Adapter, with plane male end and female Rp thread

Model 2612 : Adapter, with female end and female Rp thread

Model 2612.3 : Adapter, with female end and female Rp thread

Model 2615 : Coupling, female/female end

Model 2613 : Coupling, plain male/female end

Model 2615.5 : Sliding coupling, with female/female end

Model 2615.1 : Reducer, with female and male plain end

Model 2615.2 : Reducer, with female/female end

Model 2656 : Cap, female end

Model 2657 : Cap, male end

Model 2625.5 : Wall plate with female end and female Rp thread

Model 2659.5 : Flange adapter, female end

Equipped with B3-3785 or B3-3786 sealing


Scope :
Domaine d'application :
Toepassingsgebied :

- Low and medium pressure gas installations according to the standards NBN D51-003, NBN D51-004 and NBN D51-006
- Installations basse et moyenne pression suivant les normes NBN D51-003, NBN D51-004 et NBN D51-006
- Lage en midden druk gasinstallaties volgens de normen NBN D51-003, NBN D51-004 en NBN D51-006

Ø Copper tube and press fittings Ø Tuyau en cuivre et raccords à sertir Ø Koperen buis en persfitting	12	15	18	22	28	35	42	54
Minimum wall thickness copper tube Epaisseur de paroi minimale du tuyau en cuivre Minimum wanddikte van de koperen buis	1	1	1	1	1	1,2	1,2	1,5

Requirements:
Exigences :
Eisen :

- DVGW G 5614 'Unlösbare Rohrverbindungen für metallene Gasleitungen; Pressverbinder'
- DVGW Certificate – nr. DG 4550AU0070
 - MPM Prüfbericht – nr. 12000131 (06.08.2020)
 - MPM Prüfbericht – nr. 12005093 (07/08/2018)



Olivier THIBAUT
Laboratory Manager.