



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4312BM0092**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Distributor</b> <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Product Category</b> <i>Produktart</i>	Gas fittings: Shut-off valve <= MOP 5 (4312)
<b>Product description</b> <i>Produktbezeichnung</i>	ball valve
<b>Model</b> <i>Modell</i>	G2101
<b>Test reports</b> <i>Prüfberichte</i>	Supplement test: 160 493a E1/18213 from 06.02.2023 (GWI) Type testing: 160493T0/17749 from 15.05.2018 (GWI)
<b>Test basis</b> <i>Prüfgrundlagen</i>	DIN EN 331 (01.04.2016) DVGW CERT ZP 4110 (29.09.2022)

**Date of Expiry / File No.** 14.03.2026 / 22-0630-GNA  
**Ablaufdatum / Aktenzeichen**

14.03.2023 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

*G. Schmidt*



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-05

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Gas Category</b> <i>Gasart</i>	<b>Remarks</b> <i>Bemerkungen</i>
--------------------------------------	--------------------------------------

Fuel gases according to G  
260: 03.2013

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
G2101	Nominal pressure rating: MOP 5/C 1 Nominal diameter: DN 15	
G2101	Nominal pressure rating: MOP 5/C 1 Nominal diameter: DN 20	
G2101	Nominal pressure rating: MOP 5/C 1 Nominal diameter: DN 25	
G2101	Nominal pressure rating: MOP 5/C 1 Nominal diameter: DN 32	
G2101	Nominal pressure rating: MOP 5/C 1 Nominal diameter: DN 40	
G2101	Nominal pressure rating: MOP 5 Nominal diameter: DN 50	

#### **Hints of Utilization / Remarks**

##### ***Verwendungshinweise / Bemerkungen***

Connection type: female thread on both sides Rp 1/2...Rp 2 according to DIN EN 10226-1  
Thermal load capacity for nominal diameters DN 15 until DN 40: +650 °C at operating pressure up to 1 bar, class: C 1  
Ambient temperature range to: -20...+60 °C

DVG