



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4312DM0692

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	Gas fittings: Shut-off valve <= MOP 5 (4312)
Product description <i>Produktbezeichnung</i>	Megapress G- straight pattern ball valve with press connection and SC-Contur, leaking in unpressed state
Model <i>Modell</i>	4675; 4675.4
Test reports <i>Prüfberichte</i>	Type testing: 164 603a T0/18124 from 09.12.2021 (GWI) Supplement test: 164 603a E1/18205 from 24.11.2022 (GWI)
Test basis <i>Prüfgrundlagen</i>	DIN EN 331 (01.04.2016) DVGW CERT ZP 4110 (29.09.2022)

70089-04 DE

Date of Expiry / File No. 09.12.2026 / 20-0217-GNE
Ablaufdatum / Aktenzeichen



13.03.2023 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

G. Schmidt

DAkkS
Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
Fuel gases according to G 260	(01.09.2021)

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 15	
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 20	
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 25	
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 32	
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 40	
4675; 4675.4	Nominal pressure rating: MOP 5/ B 5 Nominal diameter: DN 50	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
4675	connection: on both sides pressing connection according to DVGW-G 5614(-B1) for steel pipes according to DIN EN 10255, DIN EN 10216-1 and DIN EN 10217-1
4675.4	connection: at the input side internal thread Rp 1/2...Rp 2 according to DIN EN 10226-1; at the outlet side pressing connection according to DVGW-G 5614(-B1) for pipes made of DIN EN 10255, DIN EN 10216-1 and DIN EN 10217-1

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Ambient temperature range: -20...+60 °C

Higher Thermal Resistance: +650 ° C up to a maximum operating pressure of 5 bar (class: B5)

installation position: any