



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-6102BT0068

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	stop valves for drinking water: Ball valve (6102)
Product Description <i>Produktbezeichnung</i>	Easytop ball valve made of red brass or silicium bronze with compression connections and SC-contour, unpressed leaky, or internal thread Rp according to EN 10226-1, or external thread G according to ISO 228
Model <i>Modell</i>	Easytop-Kugelhahn
Test Reports <i>Prüfberichte</i>	laboratory control test: 120003396-21-PB from 19.08.2021 (MPM) type testing: 120004828 from 19.12.2016 (MPM) supplement test: 120004310-1 from 27.07.2014 (MPM) supplement test: 120003824 from 22.02.2012 (MPM) hygiene: HW-0804DN0171 from 20.04.2022 (ZGW)
Test Basis <i>Prüfgrundlagen</i>	DVGW W 570-1 (01.03.2013) DIN EN 13828 (01.12.2003) UBA BWGL-Metalle (14.05.2020) UBA ELASTOM (16.03.2016) UBA Übergangsregelung KTW-BWGL (10.07.2020) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	07.02.2028 / 22-0750-WNV



25.11.2022 GI A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
21..; 53..; 22..	noise emission class: I nominal diameter: DN 15	pressure rating: PN 10
21..; 53..; 22..	noise emission class: I nominal diameter: DN 20	pressure rating: PN 10
21..; 53..; 22..	noise emission class: I nominal diameter: DN 25	pressure rating: PN 10
21..; 53..; 22..	noise emission class: I nominal diameter: DN 32	pressure rating: PN 10
21..; 53..; 22..	nominal diameter: DN 40	pressure rating: PN 10
21..; 53..; 22..	nominal diameter: DN 50	pressure rating: PN 10

Type Variation Ausführungsvariante	Explanations Erläuterungen
2170	connections: both-sided Sanfix P-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
5370	connections: both-sided Raxofix-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
5375	connections: both-sided Raxofix-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
2270	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
2275	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
2275CO	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; with mounting CO; dimensions: DN 15 - DN 50
2275.3	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; dimensions: DN 15 - DN 50
2275LF	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; LABS washed free; dimensions: DN 15 - DN 50
2270.1	connections: both-sided external thread G according to ISO 228; dimensions: DN 15 - DN 50
2275.1CO	connections: both-sided external thread G according to ISO 228; with mounting CO; dimensions: DN 15 - DN 50
2275.1	connections: both-sided external thread G according to ISO 228; dimensions: DN 15 - DN 50
2275.6	connections: both-sided external thread G according to ISO 228; dimensions: DN 15 - DN 50
2270.2	connections: both-sided internal thread Rp according to EN 10226-1; dimensions: DN 15 - DN 50
2275.2	connections: both-sided internal thread Rp according to EN 10226-1; dimensions: DN 15 - DN 50
2275.2LF	connections: both-sided internal thread Rp according to EN 10226-1; LABS washed free; dimensions: DN 15 - DN 50
2275.5	connections: both-sided internal thread Rp according to EN 10226-1; dimensions: DN 15 - DN 50
2270.4	connections: one side Sanpress-compression connectors with SC-contour, unpressed leaky, one side internal thread Rp according to EN 10226-1; dimensions: DN 15 - DN 50
2275.4	connections: one side Sanpress-compression connectors with SC-contour, unpressed leaky, one side internal thread Rp according to EN 10226-1; dimensions: DN 15 - DN 50
2275.4CO	connections: one side Sanpress-compression connectors with SC-contour, unpressed leaky, one side internal thread Rp according to EN 10226-1; with mounting CO; dimensions: DN 15 - DN 50
2270.10	connections: both-sided Sanpress-compression connectors with SC-contour, unpressed leaky; actuating lever: made of steel; dimensions: DN 15 - DN 50
2275.7	connections: one side Sanpress-compression connectors with SC-contour, unpressed leaky, one side internal thread G according to DIN EN ISO 228; dimensions: DN 15 - DN 50
2270.7	connections: one side Sanpress-compression connectors with SC-contour, unpressed leaky, one side internal thread G according to DIN EN ISO 228; dimensions: DN 15 - DN 50

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Material: Red brass (CC499K) or silicium bronze (CC246E / CuSi4Zn9MnP)

DVG