



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4360CP0083

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	Gas fittings: Gas flow monitor (4360)
Product description <i>Produktbezeichnung</i>	Gas flow monitor for buried house connection lines made of PE-HD and PE-Xa with Geopress K press connections on both sides and with overflow opening
Model <i>Modell</i>	97...
Test reports <i>Prüfberichte</i>	Laboratory control test: 157843a K2023 from 18.10.2023 (GWI) Type testing: 157843aT0/17150 from 31.03.2014 (GWI)
Test basis <i>Prüfgrundlagen</i>	DVGW G 5305-2 (01.10.2013)

Date of Expiry / File No. 31.03.2029 / 24-0162-GNV
Ablaufdatum / Aktenzeichen

150008 001 A 1 G2

15.04.2024 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

i.A. W. Thi



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
Fuel gases according to G 260: 03.2013	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
97...	Nominal flow rate: 11 (Typ R), 10 (Typ A/D und C) m ³ /h Nominal diameter: DN 25	
97...	Nominal flow rate: 16 (Typ R), 13 (Typ A/D und C) m ³ /h Nominal diameter: DN 32	
97...	Nominal flow rate: 24 (Typ R), 19 (Typ A/D und C) m ³ /h Nominal diameter: DN 40	
97...	Nominal flow rate: 34 (Typ R), 31 (Typ A/D und C) m ³ /h Nominal diameter: DN 50	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
9753.1, 9753.2	Type A/D; Operating pressure range: 25...1000 mbar
9755.1, 9755.2	Type C; Operating pressure range: 25...5000 mbar
9752.1, 9752.2	Type R; Operating pressure range: 35...5000 mbar

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Ambient temperature range: -20...+60 °C

Installation position: horizontally and vertically upwards