



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4550AU0070**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Distributor</b> <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Product Category</b> <i>Produktart</i>	Installation systems and system joints (PN 10): Compression joint for metallic gas pipes (8531)
<b>Product Description</b> <i>Produktbezeichnung</i>	Profipress G compression joint for pipes made of copper according to GW 392, leaky in the non-pressed state
<b>Model</b> <i>Modell</i>	26...
<b>Test Reports</b> <i>Prüfberichte</i>	Type testing: 120005093 from 07.08.2018 (MPM) Laboratory control test: 120000428-22-2-IB from 06.09.2022 (MPM)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DVGW G 5614 (01.12.2013)

**Date of Expiry / File No.** 31.01.2028 / 23-0081-GNV  
*Ablaufdatum / Aktenzeichen*

09.02.2023 Kir A-1/2

Date, Issued by, Sheet, Head of Certification Body  
*Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle*



DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
...11/11.5/12/12.3/14/14.2/15/ 15.5/16/16.1/18/25.5/26(.1)	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 12 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 0,8 mm and 1,0 mm
...11/11.5/12/12.3/13/14/14.2/ 15(.1/5)/16/16.1/17.2/18/25. 5/26/26.1/50/52/54/56/61	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 15 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,0 mm
...11/11.5/12/12.3/13/14/14.2/ 15(.1/5)/16/16.1/17.2/18/25. 5/26/26.1/50/52/54/56	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 18 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,0 mm
...11/11.5/12/12.3/13/14(.2/6 )/15(.1/5)/16(.1)/17.2/18(.1)/ 25.5/26/26.1/50/52/54/56/61	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 22 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,0 mm
...11/11.5/12/12.3/13/14(.2/6 )/15(.1/5)/16/16.1/17.2/18/26 (.1)/50/52/54/56/59.5/61/66	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 28 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,0 mm and 1,5 mm
...11/11.5/12/12.3/13/14/14.2/ 15(.1/5)/16/16.1/17.2/18/26/ 26.1/59.5/50/52/54/56	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 35 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,2 mm and 1,5 mm
...11/11.5/12/12.3/14/14.2/15( .1/5)/16/16.1/17.2/18/26/26.1 /59.5/50/52/54/56	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 42 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,2 mm and 1,5 mm
...11/11.5/12/12.3/14/14.2/15( .1/5)/16/16.1/17.2/18/26/26.1 /59.5/50/52/54/56	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 54 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 1,5 mm and 2,0 mm
...XL	Nominal pressure rating: MOP 5 / GT 1 Nominal diameter: da: 64 mm Ambient temperature range: -20...+70 °C	wall thickness/copper pipe: 2,0 mm

Type Variation Ausführungsvariante	Explanations Erläuterungen
...17.2	tee, thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)
...11; ...11.5	transition, thread R... DIN EN 10226-1 or G... ISO 228-1 (material: red brass or silicon bronze)
...12; ...12.3	transition, thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)
...15; ...15.5	coupling, push coupling (material: copper, red brass or silicon bronze)
...15.1	reducer (material: copper)
...13	transition, compressing joints (material: red brass or silicon bronze)
...61	conical screw connection; thread R... ISO 228-1/E DIN 3436 (material: red brass or silicon bronze)
...56	cap (material: copper)
...25.5	wall disc, thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)
...50	straight screw connection (material: red brass or silicon bronze)
...52	screw connection with femal thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)
...54	screw connection with male thread R... DIN EN 10226-1 (material: red brass or silicon bronze)
...16.1	90°-bow, pipe nozzle for pressing joints (material: copper)
...14.2	90°-bow, thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)
...26.1	45°-bow, pipe nozzle for pressing joints (material: copper)
...18.1	tee; da: 22x15x22 mm (material: copper)
...66	flange sealing screw connection (material: red brass or silicon bronze)
...59.5	transition to flange with backing ring (material: red brass or silicon bronze)
...14.6	90°-bow, thread Rp... DIN EN 10226-1 (material: red brass or silicon bronze)

### Hints of Utilization / Remarks

#### Verwendungshinweise / Bemerkungen

The requirements for Higher Thermal Resistance (HTB) are fulfilled up to pressure GT 1.

Pipes: Copper pipes according to GW 392 in qualities "hard" (da 12 - 64 mm), "half hard" (da 15 - 28 mm) and "soft" (da 12 - 22 mm)

Pressing tool: Model Viega GmbH & Co. KG with pressing jaw (model Nussbaum/Viega)

Compression joints: Red brass (CC499K) or silicon bronze (CC246E/CuSi4Zn9MnP), dimensions: 12.0 mm - 64.0 mm, type M-MM, Viega GmbH & Co. KG