



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-6110BO0004

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	Stop valves for drinking water: Inclined seat valve (6110)
Product description <i>Produktbezeichnung</i>	Easytop-inclined seat valve made of red brass or silicium bronze, with compression connectors and SC-contour, unpressed leaky, or with internal thread Rp according to EN 10226-1, or with external thread G according to ISO 228
Model <i>Modell</i>	Easytop-Schrägsitzventil
Test reports <i>Prüfberichte</i>	Supplement test: 2-0180/23 from 08.01.2024 (TZW) Laboratory control test: 2-0103/22 from 27.09.2022 (TZW) Type testing: TA 013/14 from 25.08.2014 (TZW) Hygiene: Z-341449-21-Hy112 from 15.03.2021 (WHY)
Test basis <i>Prüfgrundlagen</i>	DVGW W 570-1 (01.03.2013) DIN EN 1213 (01.12.1999) UBA BWGL-Metalle: Grundwerkstoffe (11.01.2023) UBA ELASTOM (16.03.2016) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	07.01.2028 / 23-0448-WNA

70028 04 A CE

27.05.2024 Fk A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

P. Schmidt



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
2137, 2237, 2237.1, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Noise emission class: I Pressure rating: PN 10/16 Nominal diameter: DN 15	
2137, 2237, 2237.1, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Noise emission class: I Pressure rating: PN 10/16 Nominal diameter: DN 20	
2137, 2237, 2237.1, 2230.50, 2230.51, 2230.55, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Noise emission class: I Pressure rating: PN 10/16 Nominal diameter: DN 25	
2137, 2237, 2237.1, 2230.50, 2230.51, 2230.55, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Noise emission class: I Pressure rating: PN 10/16 Nominal diameter: DN 32	
2137, 2237, 2237.1, 2230.50, 2230.51, 2230.55, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Pressure rating: PN 10/16 Nominal diameter: DN 40	
2137, 2237, 2237.1, 2230.50, 2230.51, 2230.55, 5337, 2237.5, 2237.3, 2230.52, 2230.53, 5337.5, 2237.2	Pressure rating: PN 10/16 Nominal diameter: DN 50	

Type Variation Ausführungsvariante	Explanations Erläuterungen
2237; 2237.5	type of connection: Sanpress-compression connectors with SC-contour, unpresseed leaky
2237.1; 2237.3	type of connection: external thread G according to ISO 228
2137	type of connection: Sanfix P-compression connectors with SC-contour, unpresseed leaky
2230.50; 2230.52	type of connection: Sanfix P-compression connectors with SC-contour, unpresseed leaky, internal thread Rp according to EN 10226-1
2230.51; 2230.53; 2237.2	type of connection: internal thread Rp according to EN 10226-1
2230.55	type of connection: Geopress-compression connectors with SC-contour, unpresseed leaky, internal thread Rp according to EN 10226-1
5337; 5337.5	type of connection: Raxofix-compression connectors with SC-contour, unpresseed leaky

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

material: red brass (CC499K) or silicium bronze (CC246E / CuSi4Zn9MnP)

DWG