



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4511CP0649
Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	Pipe equipment and fittings: Tapping valve for HDPE pipes (4511)
Product description <i>Produktbezeichnung</i>	Drilling fitting made of glass fibre reinforced polyamide for gas supply lines made of PE 80, PE 100, PE-Xa, PE-Xb and PE-Xc
Model <i>Modell</i>	969...G
Test reports <i>Prüfberichte</i>	Laboratory control test: RA4707.229233.23 from 25.04.2023 (SKZ) Type testing: 108526/13-II from 20.03.2014 (SKZ)
Test basis <i>Prüfgrundlagen</i>	DIN 3588-1 (01.11.2021) DIN 3588-3 (01.11.2021)

Date of Expiry / File No. 20.03.2028 / 23-0302-GNA
Ablaufdatum / Aktenzeichen

03.08.2023 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 63 mm	
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 90 mm	
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 110 mm	
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 125 mm	
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 140 mm	
969...G	Nominal pressure rating: PN 4/8/10 Nominal diameter (supplying pipe): 160 mm	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
9690 G	with operating shut-off
9692 G	without operating shut-off
969...G	for the connection of Geopress G- or Geopress K gas-connection pieces.

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Nominal diameters of the supply line: 63 mm, 90 mm, 110 mm, 125 mm, 140 mm, 160 mm, 180 mm, 200 mm und 225 mm.

Can be used for the following supply lines:

Pipes made of PE 80; DVGW GW 335-Teil A2, maximum operating pressure: 4 bar

Pipes made of PE 100; DVGW GW 335-Teil A2, maximum operating pressure: 10 bar

Pipes made of PE-Xa; DVGW GW 335-Teil A3, maximum operating pressure : 8 bar

Pipes made of PE-Xb and PE-Xc; DVGW VP 640, maximum operating pressure: 8 bar

Connection pipe: Typ 969...G, 32 mm, 40 mm, 50 mm, 63 mm: Nominal pressure PN 4/8/10

The testing and certification of the listed Drilling fittings was carried out for pipes made of PE-Xb und PE-Xc.