



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-6110B00003

Registration Number
Registrierungsnummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	stop valves for drinking water: inclined seat valve (61110)
Product Description <i>Produktbezeichnung</i>	Easytop-inclined seat valve with backflow preventer (KRV-valve) made of red brass or silicium bronze, with compression connectors and SC-contour, unpressed leaky, or with internal thread Rp according to EN 10226-1, Easytop-KRV-Ventil
Model <i>Modell</i>	
Test Reports <i>Prüfberichte</i>	laboratory control test: 2-0103/22 from 27.09.2022 (TZW) type testing: RV 002/16 from 14.09.2016 (TZW) type testing: RV 006/14 from 25.08.2014 (TZW) type testing: 0207-4530, 0210-4549 from 09.12.2008 (SVG) UBA-Guideline: Z-341449-21-Hy112 from 15.03.2021 (WHY)
Test Basis <i>Prüfgrundlagen</i>	DVGW W 570-1 (01.03.2013) DIN EN 1213 (01.12.1999) DIN EN 13959 (01.01.2005) UBA BWGL-Metalle (14.05.2020) UBA ELASTOM (16.03.2016) DVGW W 270 (01.11.2007)

Date of Expiry / File No. 07.01.2028 / 22-0770-WNV
Ablaufdatum / Aktenzeichen

70028 04 A DE

16.11.2022 LE A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

G. Schmidt



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel.: +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type	Technical Data	Remarks
Typ	Technische Daten	Bemerkungen
2138, 2238, 2238.1, 5338,	noise emission class: I	
2230.92, 2238.5, 2238.3,	pressure rating: PN 10	
5338.5	nominal diameter: DN 15	
2138, 2238, 2238.1, 5338,	noise emission class: I	
2230.92, 2238.5, 2238.3,	pressure rating: PN 10	
5338.5	nominal diameter: DN 20	
2138, 2230.91, 2238, 2238.1,	noise emission class: I	
5338, 2230.92, 2238.5,	pressure rating: PN 10	
2238.3, 5338.5	nominal diameter: DN 25	
2138, 2230.91, 2238, 2238.1,	noise emission class: I	
5338, 2230.92, 2238.5,	pressure rating: PN 10	
2238.3, 5338.5	nominal diameter: DN 32	
2138, 2230.91, 2238, 2238.1,	pressure rating: PN 10	
5338, 2230.92, 2238.5,	nominal diameter: DN 40	
2238.3, 5338.5		
2138, 2230.91, 2238, 2238.1,	pressure rating: PN 10	
5338, 2230.92, 2238.5,	nominal diameter: DN 50	
2238.3, 5338.5		

Type Variation	Explanations
Ausführungsvariante	Erläuterungen
2138	type of connection: Sanfix P-compression connectors with SC-contour, unpressed leaky
2230.91; 2230.92	type of connection: internal thread Rp according to EN 10226-1
2238; 2238.5	type of connection: Sanpress-compression connectors with SC-contour, unpressed leaky
2238.1; 2238.3	type of connection: external thread G according to ISO 228
5338; 5338.5	type of connection: Raxofix-compression connectors with SC-contour, unpressed leaky

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

material: red brass (CC499K) or silicon bronze (CC246E / CUSi4Zn9MnP)

DWG