



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DW-6110BO0003**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Distributor</b> <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Product Category</b> <i>Produktart</i>	Stop valves for drinking water: Inclined seat valve (6110)
<b>Product description</b> <i>Produktbezeichnung</i>	Easytop-inclined seat valve with backflow preventer (KRV-valve) made of red brass or silicium bronze, with compression connectors and SC-contour, unpressed leaky, or with internal thread Rp according to EN 10226-1,
<b>Model</b> <i>Modell</i>	Easytop-KRV-Ventil
<b>Test reports</b> <i>Prüfberichte</i>	Supplement test: 2-0181/23 from 08.01.2024 (TZW) Laboratory control test: 2-0103/22 from 27.09.2022 (TZW) Type testing: RV 002/16 from 14.09.2016 (TZW) Hygiene: Z-341449-21-Hy112 from 15.03.2021 (WHY)
<b>Test basis</b> <i>Prüfgrundlagen</i>	DVGW W 570-1 (01.03.2013) DIN EN 1213 (01.12.1999) DIN EN 13959 (01.01.2005) UBA BWGL-Metalle: Grundwerkstoffe (11.01.2023) UBA ELASTOM (16.03.2016) DVGW W 270 (01.11.2007)
<b>Date of Expiry / File No.</b> <i>Ablaufdatum / Aktenzeichen</i>	07.01.2028 / 23-0448-WNA

27.05.2024 Fk A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
2138, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Noise emission class: I Pressure rating: PN 10 Nominal diameter: DN 15	
2138, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Noise emission class: I Pressure rating: PN 10 Nominal diameter: DN 20	
2138, 2230.91, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Noise emission class: I Pressure rating: PN 10 Nominal diameter: DN 25	
2138, 2230.91, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Noise emission class: I Pressure rating: PN 10 Nominal diameter: DN 32	
2138, 2230.91, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Pressure rating: PN 10 Nominal diameter: DN 40	
2138, 2230.91, 2238, 2238.1, 5338, 2230.92, 2238.5, 2238.3, 5338.5, 2238.2	Pressure rating: PN 10 Nominal diameter: DN 50	

Type Variation Ausführungsvariante	Explanations Erläuterungen
2138	type of connection: Sanfix P-compression connectors with SC-contour, unpresseed leaky
2230.91; 2230.92; 2238.2	type of connection: internal thread Rp according to EN 10226-1
2238; 2238.5	type of connection: Sanpress-compression connectors with SC-contour, unpresseed leaky
2238.1; 2238.3	type of connection: external thread G according to ISO 228
5338; 5338.5	type of connection: Raxofix-compression connectors with SC-contour, unpresseed leaky

#### Hints of Utilization / Remarks

#### Verwendungshinweise / Bemerkungen

material: red brass (CC499K) or silicium bronze (CC246E / CuSi4Zn9MnP)

DWG