DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-6103CM0261
Registration Number
Registriernummer

Field of Application ***Anwendungsbereich***	products of water supply *Produkte der Wasserversorgung*
Owner of Certificate ***Zertifikatinhaber***	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor ***Vertreiber***	Viega Deutschland GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category ***Produktart***	Stop valves for drinking water: Flush mounting valve (6103)
Product description ***Produktbezeichnung***	Easytop concealed straight seat valve made of red brass or silicium bronze, with compression connectors and SC-contour, unpressed leaky, or with internal thread Rp according to EN 10226-1
Model ***Modell***	Easytop-UP-Geradsitzventil
Test reports ***Prüfberichte***	Laboratory control test: 2-0061/24 from 26.08.2024 (TZW) Type testing: TA 015/17 from 16.06.2017 (TZW) Type testing: TA 062/15 from 07.12.2015 (TZW) Type testing: TA 014/14 from 25.08.2014 (TZW) Type testing: 0501-4924 from 07.07.2011 (SVG)
Test basis ***Prüfgrundlagen***	DVGW W 570-1 (01.03.2013) DIN EN 1213 (01.12.1999)
Date of Expiry / File No. ***Ablaufdatum / Aktenzeichen***	07.07.2031 / 26-0903-WNV

70028-04-A-DE

27.05.2026 Le A-1/2
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DAkkS
Deutsche
Akkreditierungsstelle
D-ZE-16028-01-00

DVGW CERT GmbH
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 9188-888
info@dvgw-cert.com
www.dvgw-cert.com

Type ***Typ***	**Technical Data** ***Technische Daten***	**Remarks** ***Bemerkungen***
2235.2; 2235.3; 5335.2	Noise emission class: I Nominal pressure rating: PN 10 Nominal diameter: DN 15	
2134.2; 2235.2; 2235.3; 5335.2	Noise emission class: I Nominal pressure rating: PN 10 Nominal diameter: DN 20	
2231.3; 2231.03; 2231.04; 2231.4; 2231.11; 2231.13; 2231.14	Noise emission class: I Nominal pressure rating: PN 10 Nominal diameter: DN 20	with integrated concealed submetering system

Type Variation ***Ausführungsvariante***	**Explanations** ***Erläuterungen***
2134.2	type of connection: Sanfix P-compression connectors with SC-contour, unpressed leaky
2235.2	type of connection: Sanpress-compression connectors with SC-contour, unpressed leaky
5335.2	type of connection: Raxofix-compression connectors with SC-contour, unpressed leaky
2231	type of connection: Sanpress-compression connectors with SC-contour, unpressed leaky
2231.4; 2235.3	type of connection: internal thread Rp according to EN 10226-1
2231.01; 2231.03	type of connection: Sanpress-compression connectors with SC-contour, unpressed leaky, insulated
2231.11; 2231.13	type of connection: internal thread Rp according to EN 10226-1, insulated
2231.04	type of connection: Sanpress-compression connectors with SC-contour, unpressed leaky, 2 valves in one insulationunit
2231.12: 2231.14	type of connection: internal thread Rp according to EN 10226-1, 2 valves in one insulationunit

Hints of Utilization / Remarks
Verwendungshinweise / Bemerkungen

material: red brass (CC499K) or silicium bronze (CC246E / CuSi4Zn9MnP)

Suitability for drinking water hygiene is verified with a "Hygiene confirmation of conformity" in accordance with the currently valid legal basis.