



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DG-4641BQ0260**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Distributor</b> <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
<b>Product Category</b> <i>Produktart</i>	gas installation components : Safety gas hose for outdoor use (4641)
<b>Product Description</b> <i>Produktbezeichnung</i>	safety gas hose from variation "M" with connector for safety gas connection valve according to DIN 3383-1, also suitable for outdoor installation
<b>Model</b> <i>Modell</i>	G2023
<b>Test Reports</b> <i>Prüfberichte</i>	laboratory control test: 154933f K2021 from 26.11.2021 (GWI) laboratory control test: 154 933f K2019 from 12.11.2019 (GWI) type testing: B 09/08/1155 from 24.08.2009 (DBI)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DIN 3383-1 (01.08.2013)

**Date of Expiry / File No.** 26.01.2027 / 21-0736-GNV  
**Ablaufdatum / Aktenzeichen**

29.06.2022 Fk A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

**Gas Category**

Remarks

Gasart Bemerkungen

fuel gases according to G 260

**Type**

Technical Data

Remarks Bemerkungen

G2023

nominal diameter: DN 15  
max. operating pressure: 100 mbar

**Type Variation**

Explanations

Ausführungsvariante

G2023

connection: at the input side connector in passage form, at the output side thread socket  
with internal thread Rp 1/2 according to DIN EN 10226-1

**Hints of Utilization / Remarks**

Verwendungshinweise / Bemerkungen

classification according to DIN 3383-1: 2013, Table 1: AMS

ambient temperature range: -20 up to +135 °C

nominal length: 0,5 m, 0,75 m, 1,0 m, 1,25 m, 1,5 or 2,0 m; for commercial and industrial purposes as well as for outdoor

installation also 2,0 m, 2,5 m, 3,0 m, 3,5 m, 4,0 m, 4,5 m, 5,0 m or 6,0 m

reinforcement: protective hose made of stainless steel

sheath: plastic

