



Certificate number: 2206704 (1)

Issued 07/06/2022

Expires 07/06/2027

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Viega GmbH & Co. KG.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> to ensure that the certificate is still valid.

# CERTIFICATE

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

**Certificate Issued to:**  
Viega GmbH & Co KG  
Viega Platz 1  
57439 Attendorn  
Germany



# Product Certificate

Appendix to Certificate number: 2206704

The following products belong to this certificate

<p><b>PRODUCT DESCRIPTION</b>  Range of end feed copper or gunmetal solder fittings for use with copper pipe manufactured to EN1057  ATS3 – Without Production Surveillance</p>
<p><b>MODEL(S)</b>  95002A elbow 90° soldered connection;  95001A elbow 90° soldered connection plug-in end;  95041 elbow 45° soldered connection;  95040 elbow 45° soldered connection plug-in end;  95090 elbow 90° soldered connection;  95092 elbow 90° soldered connection plug-in end;  95130 T-piece soldered connection;  95085 crossover soldered connection;  95086 crossover soldered connection plug-in end;  95270 coupling soldered connection;  95240 reducing coupling soldered connection;  95243 reducer, plug-in end, soldered connection;  95301 cap soldered connection;  94130G T-piece soldered connection Rp-thread;  94243G adapter soldered connection Rp-thread;  94472G wall plate soldered connection Rp-thread;  94090G adapter elbow 90° soldered connection, Rp-thread;  94280G adapter plug-in end R-thread;  94270G adapter soldered connection Rp-thread;  94246G plug-in piece plug-in end, Rp-thread;  94092G adapter elbow 90° soldered connection R-thread;  94340 screw fitting soldered connection;  94471G wall plate soldered connection Rp-thread;  94096G adapter union 90°;  94340G adapter union.</p>
<p><b>SIZE:</b>  8,10,12,14,15,16,18,22,28,35,42,54,64,76.1,88.9 &amp; 108mm.</p>
<p><b>SCOPE:</b>  Manufacturer recommended maximum working pressure: Sizes 8 - 28mm: Maximum working pressure 16.0 bar. Sizes 35 - 108mm: Maximum working pressure 10.0 bar &amp; maximum operating temperature 100°C.  Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.  Above ground use only.</p>
<p><b>MARKING</b>  Fitting body stamped Viega &amp; Size.</p>
<p><b>MATERIALS</b>  Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p><b>BACKFLOW PROTECTION NOTES</b>  N/A.</p>
<p><b>ADDITIONAL NOTES</b>  All water contact &amp; exposed components satisfy opacity requirements.</p>

## Extra Notes