



KOMO®
Technical approval-with-product certificate
K93117/03



Issued 2021-06-01 Replaces K93117/02
 Valid until Indefinite Dated 2018-04-01
 Page 1 of 3

Viega Smartpress system with multilayer pipes Pexfit Fosta

Viega GmbH & Co. KG

STATEMENT BY KIWA

This technical approval-with-product certificate on the basis of BRL 5606 Plastics piping systems of PE-X intended for heating installations: radiator connections issued on 25 October 2016 by Kiwa, in accordance with the Kiwa Regulation for Certification.

The quality system and the product characteristics belonging to the Viega Smartpress system with multilayer pipes Pexfit Fosta are checked periodically and the performance of the Viega Smartpress system with multilayer pipes Pexfit Fosta in the application as radiator connections is assessed. The basic principles for the assessment are checked periodically.

Based on this Kiwa declares that :

- legitimate confidence exists that the by the holder of the technical approval- with-product certificate delivered Viega Smartpress system with multilayer pipes Pexfit Fosta comply with:
 - the technical specifications as laid down in this technical approval-with-product certificate;
 - the product requirements as laid down in this technical approval-with-product certificate, provided that the Viega Smartpress system with multilayer pipes Pexfit Fosta has been marked the with the KOMO®-mark in the manner as indicated in this technical approval-with-product certificate;
- the Viega Smartpress system with multilayer pipes Pexfit Fosta provides the performances as described in this KOMO technical approval-with-product certificate, provided that:
 - the application conditions and technical specifications as described in this KOMO approval-with-product certificate are met;
 - the manufacturing takes place according to the processing methods as laid down in this technical approval-with-product certificate.

Within the framework of this KOMO technical approval-with-product certificate there are no inspections with regard to the production of other parts of the Viega Smartpress system with multilayer pipes Pexfit Fosta or the processing of the Viega Smartpress system with multilayer pipes Pexfit Fosta.

Ron Scheepers
 Kiwa

This technical approval-with-product certificate is also included on the KOMO foundation websites: www.komo.nl and www.komo-online.nl.

Users of this technical approval-with-product certificate is advised to check whether it is still valid. For this purpose consult the website of Kiwa: www.kiwa.nl.

Kiwa Nederland B.V.
 Sir Winston Churchilllaan 273
 Postbus 70
 2280 AB RIJSWIJK
 The Netherlands
 Tel. +31 88 998 44 00
 Fax +31 88 998 44 20
 NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Certificate holder
 Viega Technology GmbH & Co. KG
 Viega Platz 1
 57439 ATTENDORN
 Postfach 430/440
 57428 ATTENDORN
 Germany
 Tel. (0) 2722 61-0
 Fax (0) 2722 / 61-94 1262
 info@viega.de
www.viega.de



Assessed is:

- Quality system
- Product
- Performance in the application
- Periodic control

CERTIFICATE

474200612

Viega Smartpress system with multilayer pipes Pexfit Fosta

TECHNICAL SPECIFICATION

Subject

Viega Smartpress system with multilayer pipes Pexfit Fosta

Product characteristics

The product complies to BRL 5606 Plastic piping systems of PE-X intended for heating installations: radiator connections.

The system consists of:

- PE-X/Al Pipes manufactured by Hewing GmbH (certificate K11410);
- Stainless steel and gun metal Smartpress fittings manufactured by Viega GmbH & Co. KG. (certificate K21483);
- Corrugated protection pipes manufactured by Viega GmbH & Co. KG. (certificate K12060).

Specification

The dimensions of the pipe in the table below are part of this certificate.

Nominal outside diameter (mm)	Wall thickness (mm)	Wall thickness aluminium (mm)
16	2,0	0,2
20	2,3	0,2

Colour of the pipes: Blue inside / white outside

Grey inside / grey outside

Colour of the fittings: Bronze or silver

Markings

The products shall be marked with the KOMO® mark.

Pipes

The minimum required marking on the pipes shall be:

- KOMO (or KOMO® word mark) + class 5/ 6 bar;
- certificate number of accompanying technical approval-with-product certificate of the piping system;
- the manufacturer's name, trade name, system name or logo;
- material identification: PE-Xc;
- the build up of the pipe: PE-Xc/Al/PE;
- nominal outside diameter;
- nominal wall thickness of the pipe in mm;
- production code.

The realization of the marks is as follows: clearly, durable and indelible at intervals of not more than 2 meters.

Fittings

The minimum required marking on the fittings shall be:

- KOMO (if not possible KOMO only on the smallest packaging);
- the manufacturer's name, trade name or logo;
- nominal outside diameter of the corresponding pipe;
- production code.

Location of the marks: on every fitting.

The realization of the marks is as follows: clearly, durable and indelible.

The minimum required marking on the smallest packaging unit of the fittings shall be:

- KOMO (or KOMO® word mark);
- certificate number of the accompanying technical approval-with-product certificate of the piping system, according the marking of the belonging pipe;
- the manufacturer's name, trade name, system name or logo;
- material identification if the fitting body is made of plastics;
- nominal outside diameter and nominal wall thickness of the corresponding pipe in mm.



Viega Smartpress system with multilayer pipes Pexfit Fosta

Location of the marks: on every package.

The realization of the marks is as follows: clearly, durable and indelible on every packaging.

Protection pipes

The minimum required marking on the protection pipes shall be:

- KOMO (or KOMO[®] word mark);
- the manufacturer's name, trade name, certificate number of the protection pipe or the certificate number of the belonging technical approval (system) certificate.

The realization of the marks is as follows: clearly and indelible at intervals of not more than 2,5 m.

Logistics

Production and assembly of the system is laid down in the annex of the certification agreement.

PROCESSING

The supplier shall provide installation instructions, approved by Kiwa. A reference to these instructions shall be made at or near the packaging. The instructions are published in the Dutch language and contains at least specific information with regard to storage, transport, processing temperature and construction of the joints.

So-called "combination boilers" are often applied in individual house heating systems. In such boilers, no double separation between drinking water and heating medium exists. A leak in the single separation may result in the heating medium coming into contact with drinking water. Because of this it is important that in case additives are added to the heating medium a Kiwa product certificate for these additives has been issued.

The heat emission to the floor is dependent on the thickness of the finishing coat and the mutual distance between the pipes. The preconditions have to be clearly described in the instructions.

PERFORMANCES

1. The system is oxygen tight.
2. All joints are leak tight and possess sufficient clamp force to resist external influences.

PERFORMANCES OF THE PRODUCTS

All system components must be designed for a lifetime of 50 years at an a operating temperature profile according to class 5 of NEN-ISO 10508 and an allowable working pressure of maximum 6 bar.

The protection pipes have to protect the medium pipes for radiator connections in case the medium pipes are embedded.

RECOMMENDATION FOR THE CUSTOMER

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

Examine at delivery of the products mentioned under "processing" that they comply to the mentioned specifications.

if you should reject a delivery on the basis of the above, please contact:

- Viega GmbH & Co. KG

and, if necessary:

- Kiwa Nederland B.V.

For the proper storage, transport and processing follow the instructions given under "processing".

