



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-6340CM0223

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega Deutschland GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	valves for drinking water: thermostatic control valve (6340)
Product Description <i>Produktbezeichnung</i>	Easytop circulation regulating valve, thermostatic controled, made of red brass or silicium bronze, with compression connectors and SC-Contur (unpressed leaky) or with external thread according to ISO 228
Model <i>Modell</i>	2281...
Test Reports <i>Prüfberichte</i>	laboratory control test: TZ 009/18 from 17.06.2019 (TZW) mechanical test: TZ 001/15 from 28.08.2015 (TZW) type testing: TZ 001/10+TZ002/10 from 23.05.2011 (TZW) UBA-Guideline: KA 0197/16 from 08.07.2016 (TZW) hygienic testing: MO 105/16 from 15.06.2016 (TZW) KTW testing: KA 0281/17 from 25.07.2017 (TZW) hygienic testing: W-298922-18-SI/to from 04.06.2018 (WHY)
Test Basis <i>Prüfgrundlagen</i>	DVGW W 554 (01.03.2011) UBA BWGL-Metalle (14.05.2020) UBA ELASTOM (16.03.2016) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	23.05.2026 / 21-0183-WNV

70009-04-A-DE

31.03.2021 LE A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
2281.5; 2281.15; 2281.7; 2281.3	pressure rating: PN 10 nominal diameter: 15 mm	
2281.5; 2281.15; 2281.7; 2281.3	pressure rating: PN 10 nominal diameter: 20 mm	
Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>	
2281.5; 2281.7	with compression connectors 15 mm, 18 mm and 22 mm	
2281.15; 2281.3	external thread G 3/4" and G 1"	
Hints of Utilization / Remarks <i>Verwendungshinweise / Bemerkungen</i>		
material: red brass (CC499K) or silicium bronze (CC246E / CuSi4Zn9MnP)		