



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4606AS0432

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Distributor <i>Vertreiber</i>	Viega GmbH & Co. KG Viega Platz 1, D-57439 Attendorn
Product Category <i>Produktart</i>	Gas installation components : Safety gas connection valve for outdoor use (4640)
Product description <i>Produktbezeichnung</i>	Safety gas connection valve with integrated thermically triggered shut-off device also suitable for indoor use
Model <i>Modell</i>	G2016T
Test reports <i>Prüfberichte</i>	Type testing: 158163dT0/17173 from 18.08.2014 (GWI) Supplement test: 158163dE2/18216 from 24.11.2022 (GWI) Laboratory control test: 158163d K20191 from 20.05.2020 (GWI)
Test basis <i>Prüfgrundlagen</i>	DIN 3383-1 (01.08.2013) DIN EN 15069 (01.07.2010) DVGW CERT ZP 4110 (29.09.2022)

Date of Expiry / File No. 31.08.2026 / 22-0630-GNA
Ablaufdatum / Aktenzeichen

14.03.2023 Bd A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

G. Schmidt



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
Fuel gases according to G 260	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
G2016T	Nominal pressure rating: PN 0,2 Nominal diameter: DN 15 Ambient temperature range: -20...+60 °C	

Hints of Utilization / Remarks

Verwendungshinweise / Bemerkungen

Connections: on the input side male thread R 1/2 according to DIN EN 10226-1; on the output side plug-in socket for plug-in of a combination A of a gas safety hose according to DIN 3383-1
 Triggered temperature: +95 °C (+/- 5 K)
 Thermal capacity: +650 °C; For operating pressures up to 0,2 bar (GT 0,2)

DVGW